# Serial Matrix Printers



The 8900 Series is designed for heavy-duty, reliable operation and is ideal for shared resource use on a LAN, multiuser UNIX<sup>®</sup> computer, engineering workstation, minicomputer, or mainframe.

**Intelligent** – The 8900 Series printers adjust to the document being printed. The intelligent forms processing of these printers is unsurpassed, with leading edge technologies such as Z-Axis Control<sup>™</sup> adjustment for document thickness and Page Finder<sup>™</sup> which locates document edges. Thirty character Answerback memory (ABM) for mission critical applications.

**Sharp** – Long-life metal tear bar for a clean edge and easy form removal. Convenient features include zero tear-off, paper parking and front load bottom feed tractors. Supports legacy applications with TI 810/880 emulations. Heavy duty printhead handles six part forms and up to nine part forms in double strike mode.

**Powerful** – Control panel enables users to easily set up and configure. Two line by sixteen character liquid crystal display (LCD). Three Powerkey<sup>M</sup> function keys and twelve operation keys allow the user to quickly configure the most frequently used printer functions such as pitch, print quality, font selection, form align, form feed, form configuration and form select. Ten user definable forms.

# 8900 Series

## Model 8920

- Straight through paper path, heavy duty forms and automatic top-of-form alignment.
- Easy to use control panel with Powerkey<sup>™</sup> function simplifies operations.

## Model 8930

- Versatile printing on continuous forms or cut sheet paper.
- Four-color process ribbon mixable for seven colors.

# Intelligent Forms Processing Technology

- Z-Axis Control<sup>™</sup> provides automatic document thickness sensing and adjustment.
- Page Finder<sup>™</sup> automatically detects the top, left, and right edge of each form that is loaded. Printing always begins at the same position, relative to the edges of the document.

# Handling Tough Jobs

- Designed for heavy-duty operation.
- Multiuser environments.
- Recommended work load: 18,000 pages per month.

# **Typical Applications**

Shared-resource environments

. . . . . . . . . . . . . .

- Office printing
- Business reports, spreadsheets, color charts
- Multipart forms



5321 Buffalo Rd • Erie, PA 16510 • USA 800-570-4533 • www.fastprinters.com

# 8900 Series

#### Printing

Serial

**Printers** 

Matrix

*Technology:* Serial impact dot matrix *Printhead:* 18-pin *Speeds:* 

-	10 cpi	12 cpi	15 cpi
DP	400 cps	480 cps	600 cps
Text	240 cps		
LQ	100 cps		

#### Fonts: Courier, Gothic Options: Presenter, Prestige Elite, OCR-A, OCR-B Bar Codes:

Options: Code 3 of 9, Interleaved 2 of 5, POSTNET

- Character Sets: US ASCII 96 character set, IBM PC1, IBM PC2, Nordic PC, ISO 8859/1 Multinational, IBM Multinational
- Print Modes: Normal, bold, emphasized (shadow), expanded, compressed, underline, italics (Epson only)

*LF Interval:* <27 msec *Character Spacing:* 5, 6, 7.5, 8.3, 8.6, 10, 12, 15, 16.7, 17.1 cpi *Line Spacing:* 3, 4, 6, and 8 lpi *Print Line:* 13.6 in. *Dot Graphics (dpi):* 240H x 216V

#### Flexible Paper Handling

Paper Handling: Zero-inch tear-off, automatic top-of-form alignment, Z-Axis control (auto forms thickness adjustment), Page Finder paper edge detection, paper parking Paper Drive: 5-pin push tractors Paper Dimensions: Continuous forms: 3" to 15" W x 57" L maximum Cut sheets: 3" to 14" W x 4.5" L minimum (8930) Number of Copies:

6-part copies in standard mode 9-part copies in double strike mode Maximum Forms Thickness: 0.32" Paper Slew: 16 ips

#### **Print Control**

Formats: 10 user-defined forms

#### Emulations

TI 880,TI 855(Qume/Epson), IBM® Proprinter, Epson® FX (Escape/P), Epson JX Options: DEC LA120

#### Interfaces and Connectivity

- CENTRONICS® parallel and EIA RS-232 serial Input Buffer: 32K
- *Options:* RS-422, current loop, RS-423, MacAdapter, Ethernet 10BT

#### Physical

Size (HxWxD): 11.1 x 25.4 x 13 in. (282 x 645 x 330 mm) Weight: 52 lbs (23.6 kg) Acoustics: 61 dBa

#### **Operating Environment**

Voltage: 100-132, 200-264 VAC; 47-63 Hz, single phase Power Input: 225 watts maximum (768 BTU/hour) Storage Temperature: -22° to 150° F (-30° to 66° C] Operating Temperature: 41° to 104° F (5° to 40° C) Storage Humidity: 5% to 95% (no condensation) Operating Humidity: 10% to 90% (no condensation)

#### Reliability

MTBF: 9,000 hours @ 100% duty cycle Workload: 18,000 pages per month MTTR: 20 minutes
Printhead Life: 300 million draft characters
Ribbon Life: Black: 13 million draft characters Color: 1.5 million draft characters per band (8920C, 8930)

#### Ribbon

*Type:* Continuous loop cartridge ribbons Black: 33 yards Part number 2551152-0011 Color: 30 yards (8920C, 8930) Part number 2551152-0014 *Life:* Black: 13 million draft characters Color: 1.5 million draft characters per band (8920C, 8930)

#### Warranty

1 year return to depot

#### Options

Printer stand Stand mounted basket Printer mounted basket Acoustic cover Top feed tray (8930) Bar code/OCR font Presenter and Prestige Elite font DECLA120 RS-422 RS-423 Current loop MacAdapter Ethernet 10BT



The 8900 Ethernet interface provides a flexible solution for LAN environments.

### Features

Easy setup and administration

- Ethernet 802.3 RJ45/CAT5
- Supports Windows 95, 98, NT, 2000, UNIX and Novell
- TCP/IP, IPX/SPX, NetBEUI protocols
- BOOTP, SNMP, Telnet, TFTP, FTP, lpd, RARP, DHCP



5321 Buffalo Rd • Erie, PA 16510 • USA 800-570-4533 • www.fastprinters.com

# 8900 Series

# Printer Mounted Basket 2557749-0001



Stand Mounted Basket 2557762-0001

. . . . . . . .

# **Supplies & Options**

# Acoustic Cover 2566304-0001





Printer Stand 2557748-0001

. . . . . . . . . . . . . . . . . . .

# Interface Kits

Ethernet 10BT	
Current Loop	
RS-422	

# **Ribbons / Printheads**

Printhead 8920 / 8930	2551204-0203
Black Ribbon	2551152-0011
Color Ribbon 8930	2551152-0014

# **Option Kits**

Version 3.11 ROM Upgrade 8920	2563417-0020
Version 3.11 ROM Upgrade 8930	2563414-0030
Barcode / OCR / Postnet font 8920	2563352-0020
Barcode / OCR / Postnet font 8930	2563352-0030
Presentor & Prestige font 8920	2563351-0020
Presentor & Prestige font 8930	2563351-0030
DEC LA120 Emulation 8920	2563407-0020
DEC LA120 Emulation 8930	2563407-0030



5321 Buffalo Rd • Erie, PA 16510 • USA 800-570-4533 • www.fastprinters.com

# Serial Matrix Printers