

Serial Matrix Printer



8920 FRN

Key Features

- **Factory ReNewed** model offers the longevity, performance and reliability of new with substantial savings off the new price.
- Everything **NEW** including printer mechanism with recertified printed circuit boards.
- Standard new unit 1 year warranty.
- User manual and ribbon included.

Intelligent Forms Processing Technology

- Z-Axis Control™ provides automatic document thickness sensing and adjustment.
- Page Finder™ automatically detects the top, left, and right edge of each form that is loaded. Printing always begins at the same position, relative to the edges of the document.

Handling Tough Jobs

- Designed for heavy-duty operation.
- Multiuser environments.
- Recommended work load: 18,000 pages per month.

The 8900 Series is designed for heavy-duty, reliable operation and is ideal for shared resource use on a LAN, multiuser UNIX® computer, engineering workstation, minicomputer, or mainframe.

Intelligent – *The 8900 Series printers adjust to the document being printed. The intelligent forms processing of these printers is unsurpassed, with leading edge technologies such as Z-Axis Control™ adjustment for document thickness and Page Finder™ which locates document edges. Thirty character Answerback memory (ABM) for mission critical applications.*

Sharp – *Long-life metal tear bar for a clean edge and easy form removal. Convenient features include zero tear-off, paper parking and front load bottom feed tractors. Supports legacy applications with TI 810/880 emulations. Heavy duty printhead handles six part forms and up to nine part forms in double strike mode.*

Powerful – *Control panel enables users to easily set up and configure. Two line by sixteen character liquid crystal display (LCD). Three Powerkey™ function keys and twelve operation keys allow the user to quickly configure the most frequently used printer functions such as pitch, print quality, font selection, form align, form feed, form configuration and form select. Ten user definable forms.*

Typical Applications

- Shared-resource environments
- Office printing
- Business reports, spreadsheets, color charts
- Multipart forms



5321 Buffalo Rd • Erie, PA 16510 • USA
800-570-4533 • www.fastprinters.com

8920 FRN Printer

Serial Matrix Printer

Printing

Technology: Serial impact dot matrix

Printhead: 18-pin

Speeds:

	10 cpi	12 cpi	15 cpi
DP	400 cps	480 cps	600 cps
Text	240 cps		
LQ	100 cps		

Fonts: Courier, Gothic

Options: Presenter, Prestige Elite,
OCR-A, OCR-B

Bar Codes:

Options: Code 3 of 9, Interleaved
2 of 5, POSTNET

Character Sets: US ASCII 96 character set, IBM PC1, IBM PC2, Nordic PC, ISO 8859/1 Multinational, IBM Multinational

Print Modes: Normal, bold, emphasized (shadow), expanded, compressed, underline, italics (Epson only)

LF Interval: <27 msec

Character Spacing: 5, 6, 7.5, 8.3, 8.6, 10, 12, 15, 16.7, 17.1 cpi

Line Spacing: 3, 4, 6, and 8 lpi

Print Line: 13.6 in.

Dot Graphics (dpi): 240H x 216V

Flexible Paper Handling

Paper Handling: Zero-inch tear-off, automatic top-of-form alignment, Z-Axis control (auto forms thickness adjustment), Page Finder paper edge detection, paper parking

Paper Drive: 5-pin push tractors

Paper Dimensions:

Continuous forms: 3" to 15" W x 57" L maximum

Number of Copies:

6-part copies in standard mode

9-part copies in double strike mode

Maximum Forms Thickness: 0.32"

Paper Slew: 16 ips

Print Control

Formats: 10 user-defined forms

Emulations

TI 880, TI 855 (Qume/Epson), IBM®

Proprinter, Epson® FX (Escape/P),

Epson JX

Options: DEC LA120

Interfaces and Connectivity

CENTRONICS® parallel and EIA RS-232 serial

Input Buffer: 32K

Options: RS-422, current loop, RS-423,

MacAdapter, Ethernet 10BT

Physical

Size (HxWxD): 11.1 x 25.4 x 13 in.

(282 x 645 x 330 mm)

Weight: 52 lbs (23.6 kg)

Acoustics: 61 dBA

Operating Environment

Voltage: 100-132, 200-264 VAC;

47-63 Hz, single phase

Power Input: 225 watts maximum

(768 BTU/hour)

Storage Temperature:

-22° to 150° F (-30° to 66° C)

Operating Temperature:

41° to 104° F (5° to 40° C)

Storage Humidity: 5% to 95%

(no condensation)

Operating Humidity: 10% to 90%

(no condensation)

Reliability

MTBF: 9,000 hours @ 100% duty cycle

Workload: 18,000 pages per month

MTTR: 20 minutes

Printhead Life: 300 million draft characters

Ribbon Life:

Black: 13 million draft characters

Ribbon

Type: Continuous loop cartridge

ribbons

Black: 33 yards

Part number 2551152-0011

Life:

Black: 13 million draft characters

Warranty

1 year return to depot

Options

Printer stand

Stand mounted basket

Printer mounted basket

Acoustic cover

Bar code/OCR font

Presenter and Prestige Elite font

DECLA120

RS-422

RS-423

Current loop

MacAdapter

Ethernet 10BT



The 8900 Ethernet interface provides a flexible solution for LAN environments.

Features

- Easy setup and administration
- Ethernet 802.3 RJ45/CAT5
- Supports Windows 95, 98, NT, 2000, UNIX and Novell
- TCP/IP, IPX/SPX, NetBEUI protocols
- BOOTP, SNMP, Telnet, TFTP, FTP, lpd, RARP, DHCP

 **LAKE ERIE
SYSTEMS**
COMPUTING AND PRINTER SOLUTIONS

5321 Buffalo Rd • Erie, PA 16510 • USA
800-570-4533 • www.fastprinters.com

8920 FRN Printer

Serial
Matrix
Printer

Printer Mounted Basket 2557749-0001



Acoustic Cover 2566304-0001



Stand Mounted Basket 2557762-0001



Printer Stand 2557748-0001

Supplies & Options

Interface Kits

Ethernet 10BT	2563356-0015
Current Loop	2563356-0001
RS-422	2563356-0002

Ribbons / Printheads

Printhead	2551204-0203
Black Ribbon	2551152-0011

Option Kits

Version 3.11 ROM Upgrade	2563417-0020
Barcode / OCR / Postnet Font	2563352-0020
Presentor & Prestige Font	2563351-0020
DEC LA120 Emulation	2563407-0020



5321 Buffalo Rd • Erie, PA 16510 • USA
800-570-4533 • www.fastprinters.com