

Lexmark 2400 Series Forms Printer



- Easy-to-use 2-layer operator panel
- USB standard interface for easy connectivity
- Optional high-yield re-inking ribbon adds even greater value
- Optional Tractor 2 Feeder attaches to the front of the printer and provides the capability to load two different types of forms simultaneously

LEXMARKTM

Lexmark 2400 Series Forms Printer

- Easy-to-use 2-layer operator panel
- USB standard interface for easy connectivity
- Optional high-yield re-inking ribbon adds even greater value
- Optional Tractor 2 Feeder attaches to the front of the printer and provides the capability to load two different types of forms simultaneously



Lexmark 2480, 2481, 2490, 2491

Product Specifications

Part Number	US 12T0050 (2480), 12T0100 (2481), 12T0350 (2490), 12T0400 (2491) Canada 12T0051 (2480), 12T0101 (2481), 12T0351 (2490), 12T0401 (2491)
Technology	2480, 2481: 9-pin dot matrix; 2490, 2491: 24-pin dot matrix
Speed	2480, 2481: 510 cps in Fast Draft at 12 cpi, 438 cps in Fast Draft at 10 cpi, 309 cps in Draft at 10 cpi, 77 cps in Near Letter Quality at 10 cpi; 2490, 2491: 465 cps in Fast Draft at 12 cpi, 409 cps in Fast Draft at 10 cpi, 274 cps in Draft at 10 cpi, 91 cps in Near Letter Quality at 10 cpi
Memory	2480, 2481: 96KB; 2490, 2491: 79.5KB
Emulations	IBM PPDS emulation with euro support, Epson emulation, and optional Okidata MICROLINE emulation for 2480 and 2481 only
Connectivity	Standard: Parallel, USB Optional: Ethernet, Token-Ring, Serial, Coax/Twinax, Wireless
Resolution	2480, 2481: Near Letter Quality, 240 x 144 dpi; 2490, 2491: APA Graphics, 360 x 360 dpi
Fonts	2480, 2481: 4 resident, 7 resident bar codes (including PostNet); 2490, 2491: 8 resident, 7 resident bar codes (including PostNet)
Maximum Print Line	2480, 2490: 8 in. (203.2 mm); 2481, 2491: 13.6 in. (345.4 mm)
Operating Systems	Windows, Linux, UNIX and OS/400; For a complete list, visit www.lexmark.com
Network Support	Lexmark MarkNet™ X2000 external print servers
Usability Features	Intuitive 2-layer operator panel; Panel-selectable forms macros; Front-loading paper source; Quiet mode; Variable forms-length settings
Size (WxDxH)	2480, 2490: 19.4 in. x 11.4 in. x 7.7 in. (491.5 mm x 290 mm x 195 mm); 2481, 2491: 25 in. x 11.4 in. x 7.7 in. (633.5 mm x 290 mm x 195 mm) 21.6 lb (9.8 kg)
Weight	2480, 2490: 17.6 lb (8 kg); 2481, 2491: 21.6 lb (9.8 kg)
Acoustics	53 dBA courier front microphone position
MTBF	12,500 hours at 25% duty
Warranty	2-year LexExpress SM or customer carry-in


Media Specifications

Paper Handling	Front push/pull, bottom pull, rear push, convertible tractor, manual cut-sheet feed; Tractor 2 option allows loading of two continuous form types; Automatic sheet feeder option allows automatic feeding of cut-sheets; 2480, 2481: Up to 6-part forms in variable lengths; 3" to 22" (76 mm to 559 mm); 2490, 2491: Up to 4-part forms in variable lengths; 3" to 22" (76 mm to 559 mm)
Media Types	Continuous forms, cut sheets, labels, envelopes

Supplies & Accessories

Supplies	Standard Re-Inking Ribbon – 4 Million Characters in Draft mode at 10 cpi	11A3540
	High Yield Re-Inking Ribbon – 8 Million Characters in Draft mode at 10 cpi	11A3550
Options	Okidata MICROLINE Emulation	12T0155
Paper Handling	Automatic Sheet Feeder (2480, 2490 Narrow)	12T0150
	Automatic Sheet Feeder (2481, 2491 Wide)	12T0151
	Tractor 2 (2480, 2490 Narrow)	12T0152
	Tractor 2 (2481, 2491 Wide)	12T0153
Adapters & Cables	Coax Adapter for SCS	12T0240
	Twinax Adapter for SCS	12T0241
	Serial Interface Option	12T0154
	Parallel (10') Cable	1329605
	Parallel (20') Cable	1427498
	USB (2-meter) Cable	12A2405
	Serial (50') Cable*	1038693

In the Box



Lexmark 2480

- Lexmark 2480 Forms Printer
- 24xx Standard Yield Black Re-inking Ribbon
- Power Cord
- Quick Setup/Reference Booklet
- User's Guide
- Operator Panel Overlay

Lexmark 2481

- Lexmark 2481 Forms Printer
- 24xx Standard Yield Black Re-inking Ribbon
- Power Cord
- Quick Setup/Reference Booklet
- User's Guide
- Operator Panel Overlay

Lexmark 2490

- Lexmark 2490 Forms Printer
- 24xx Standard Yield Black Re-inking Ribbon
- Power Cord
- Quick Setup/Reference Booklet
- User's Guide
- Operator Panel Overlay

Lexmark 2491

- Lexmark 2491 Forms Printer
- 24xx Standard Yield Black Re-inking Ribbon
- Power Cord
- Quick Setup/Reference Booklet
- User's Guide
- Operator Panel Overlay

