

Order Information Chart

| Part No. | UPC | Description |
|------------------------------|-----------------|--------------------------------|
| United States | | |
| 12N1200 | 7-34646-47700-0 | Lexmark C912 |
| 12N1300 | 7-34646-47800-7 | Lexmark C912n |
| 12N1400 | 7-34646-47900-4 | Lexmark C912dn |
| 12N1500 | 7-34646-12290-0 | Lexmark C912fn |
| SUPPLIES | | |
| Cartridges | | |
| 12N0768 | 7-34646-56768-8 | Cyan Print Cartridge |
| 12N0769 | 7-34646-56769-5 | Magenta Print Cartridge |
| 12N0770 | 7-34646-56770-1 | Yellow Print Cartridge |
| 12N0771 | 7-34646-56771-8 | Black Print Cartridge |
| 12N0772 | 7-34646-56772-5 | Color Photodeveloper Kit |
| 12N0773 | 7-34646-56773-2 | Black Photodeveloper |
| 12N0774 | 7-34646-56774-9 | Oil Coating Roller |
| 11K3188 | 7-34646-20993-9 | Staple Cartridge |
| Media | | |
| 12A5940 | 7-34646-17130-4 | Transparencies (Letter) |
| 12A5950 | 7-34646-24547-0 | Glossy Paper (Letter) |
| OPTIONS AND FEATURES | | |
| Paper Handling | | |
| 12N0778 | 7-34646-56778-7 | 550-sheet Drawer |
| 12N0780 | 7-34646-56780-0 | Heavy Media Tray |
| 12N0781 | 7-34646-56781-7 | High Capacity Feeder |
| 12N0782 | 7-34646-56782-4 | 2x550-sheet Drawer with Base |
| 12N0783 | 7-34646-56783-1 | Duplex Unit |
| 12N0784 | 7-34646-56784-8 | Staple Punch Finisher(3 hole) |
| 12N0785 | 7-34646-56785-5 | Staple Punch Finisher(4 hole) |
| Memory Options | | |
| 11N0023 | 7-34646-36784-4 | 64MB SDRAM |
| 11N0025 | 7-34646-36785-1 | 128MB SDRAM |
| 11N0036 | 7-34646-36851-3 | 256MB SDRAM |
| 12P0069 | 7-34646-36855-1 | 4MB Flash DIMM |
| 12P0068 | 7-34646-36854-4 | 8MB Flash DIMM |
| 12P0066 | 7-34646-36853-7 | 16MB Flash DIMM |
| 12P0101 | 7-34646-24578-4 | Simplified Chinese Font Kit |
| 12P0102 | 7-34646-24579-1 | Traditional Chinese Font Kit |
| 12P0103 | 7-34646-24580-7 | Japanese Font Kit |
| 12N1262 | 7-34646-12347-1 | 20 + GB Hard Disk |
| APPLICATION SOLUTIONS | | |
| Optra Forms Solutions | | |
| 11N0040 | 7-34646-20731-7 | Optra Forms™ Software |
| 11N0052 | 7-34646-20732-4 | Optra Forms Director Software |
| 12P0085 | 7-34646-36846-9 | Lexmark Forms 4MB Flash DIMM |
| 12P0084 | 7-34646-36847-6 | Lexmark Forms 8MB Flash DIMM |
| 12P0083 | 7-34646-36848-3 | Lexmark Forms 16MB Flash DIMM |
| 12P0086 | 7-34646-36850-6 | Lexmark Forms Hard Disk 5 + GB |
| 43H5841 | 7-34646-17041-3 | Lexmark Forms 2-Key Security |
| 43H5842 | 7-34646-17042-0 | Lexmark Forms 3-Key Security |

| Part No. | UPC | Description |
|---|-----------------|---|
| Application Card Solutions | | |
| 12N1252 | 7-34646-26888-2 | Card for IPDS & SCS/Tne |
| 12N1250 | 7-34646-36842-1 | ImageQuick™ Card |
| 12N1251 | 7-34646-36843-8 | Bar Code Card |
| CONNECTIVITY | | |
| External Print Servers | | |
| 46D0060 | 7-34646-30316-3 | MarkNet X2011e Ethernet 10/100BaseTx – 1-port |
| 46D0040 | 7-34646-30315-6 | MarkNet X2012e Ethernet 10/100BaseTx/10Base2 – 1-port |
| 46D0020 | 7-34646-30357-6 | MarkNet X2031e Ethernet 10/100BaseTx – 3-port |
| 46D0000 | 7-34646-30313-2 | MarkNet X2030t Token-Ring – 3-port |
| 1010025 | 7-34646-11802-6 | 802.11b Wireless Print Adapter |
| Internal Print Servers | | |
| 44D0000 | 7-34646-17332-2 | MarkNet N2000 Ethernet 10/100BaseTX |
| 44D0050 | 7-34646-17334-6 | MarkNet N2000 Ethernet 10BaseT/2 |
| 44D0020 | 7-34646-17333-9 | MarkNet N2000 Token-ring |
| Internal Fiber Optic Print Servers | | |
| 44D0100 | 7-34646-30368-2 | MarkNet N2003fx SC (100MB) |
| 44D0085 | 7-34646-30367-5 | MarkNet N2003fx MTRJ (100MB) |
| OTHER ATTACHMENT OPTIONS | | |
| Adapters/Interface Cards | | |
| 11K4019 | 7-34646-36837-7 | RS0232C Serial/Parallel 1284 A-C Interface Card |
| 11K4250 | 7-34646-30811-3 | Parallel 1284 C-B Adapter |
| 11K4200 | 7-34646-30812-0 | Parallel Card (11K4019) w/1284-C Cable (11K4078) |
| 11K4300 | 7-34646-30813-7 | Parallel Card (11K4019) w/C-B Adapter (11K4250) |
| 1368705 | 7-34646-11039-0 | External Serial Adapter |
| 11K4120 | 7-34646-24573-9 | Coax/Twinax Adapter for SCS |
| Cables | | |
| 1329605 | 0-87944-09056-4 | Parallel (10') Cable |
| 1427498 | 7-34646-13068-4 | Parallel (20') Cable |
| 11K4078 | 7-34646-37011-0 | Parallel 1284 A-C (6') Cable |
| 1038693 | 7-34646-21649-4 | Serial (50') Cable |
| 12A2405 | 7-34646-18340-6 | USB (2-meter) Cable |
| MULTIFUNCTION OPTIONS | | |
| Furniture | | |
| 12N0786 | 7-34646-56787-9 | C910, C912 Printer Cabinet |
| 12N0787 | 7-34646-56788-6 | C910, C912 Printer Base |

Lexmark C912 Color Printer



Wide-format



28 ppm monochrome and color, and 19 ppm duplex quickly handles short or long run jobs to maximize productivity

High yield cartridges are specially designed to tackle the high print volumes typical of large networks

Color speed and wide format delivers a lot of print capability for a reasonable price

100,000 page maximum monthly duty cycle allows large work-group support and production printing capability in one device



LEXMARK™

Lexmark, Lexmark with diamond design, MarkNet and Optra Forms are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Passion for printing ideas is a trademark of Lexmark International, Inc. © Copyright 2003. Lexmark International, Inc. All rights reserved.

71K-XXXX

LEXMARK™

Lexmark

C912

The high speed, wide format color printer with superior print quality for high volume applications.



Lexmark C912



Lexmark C912n/C912dn

Performance

Up to 28 ppm monochrome and color, and 19 ppm duplex quickly handles short or long run jobs to maximize productivity

600 MHZ RISC processor with 128 MB RAM quickly processes large wide format color jobs for no network bottlenecks

Cost effective

Color speed and wide format delivers a lot of print capability for a reasonable price

3 levels of toner saver saves up to 50% of toner usage mono or color

Print quality

2400 image quality provides the superior color images and business graphics

Enhanced color tables provide accurate color for pre-press layouts and finished collaterals

High volume versatility

100,000 page maximum monthly duty cycle allows large workgroup support and production printing capability in one device

Production paper handling with maximum input of 5,300 sheets and output of 1,650 sheets



Lexmark C912fn

| | Lexmark C912(n)(dn)(fn) |
|---|--|
| Part Number | US/Canada 12N1200, 12N1300(n), 12N1400(dn), 12N1500(fn) |
| Technology | Color Dynamic LED |
| Speed | Up to 28 ppm monochrome and color |
| Resolution | 2400 image quality, Automatic color correction |
| Time to First Page | < 15 seconds |
| Processor | 600 MHz |
| Memory (std./max.) | 128MB/512MB (C912) 256MB/512MB (C912n), (C912dn), (C912fn) |
| Connectivity | Standard: USB support (all models), Parallel support (base model), 10/100 BaseTX Ethernet with 'n,' 'dn' and 'fn' models, supports the MarkNet™ N2000 and N2003 Series Internal Print Servers, MarkNet X2000 Series of External Print Servers Optional: RS-232C Serial/Parallel-C Interface Card, Tri-Port Adapter with RS-232/RS-422 Serial, LocalTalk and Infrared, Coax/Twinax Adapter for SCS |
| Operating Systems | Microsoft Windows 95, 98, Me, NT 4.0, 2000 and XP, Novell, UNIX and Linux, For a complete list, visit www.lexmark.com |
| Compatibility | PostScript 3 emulation standard, PCL 6 emulation standard, PPDS Migration tool standard |
| Fonts | PostScript 3 emulation, 156 scalable PCL 6 emulation, 84 scalable – 2 bitmapped PPDS Migration Tool, 39 scalable – 5 bitmapped |
| Paper Capacity Standard (in/out) Maximum (in/out) | 650/650 5,300/1,650 |
| Paper Options | Input: 550-sheet Optional Drawer, 550-sheet Heavy Media Tray, 3,000-sheet High Capacity Feeder Other: Duplex Unit |
| Paper Sources Standard (in/out) Maximum (in/out) | 2/2 6/3 |
| Media Types | Plain paper, cardstock, transparencies, envelopes, glossy paper, and paper labels |
| Media Sizes | A5, JIS B5, JIS B4, letter, legal, executive, tabloid, A3, 11.7 x 36 banner, 12 X 18, envelopes (7 3/4, 9, 10, DL, C4, C5, B5) |
| Media Weights | Standard Trays: 16-28 lb. (60-105 g/m) Multi-purpose Feeder: 16-28 lb. (60-105 g/m) Heavy Media Tray: 28-47 lb. (105-176 g/m) High Capacity Feeder: 16-28 lb. (60-105 g/m) |
| Size/Weight | C912: 27.4" x 25.8" x 20.2" (W x D x H) (695 mm x 655 mm x 512 mm) 177.1 lb. (80.5 kg) C912n: 27.4" x 25.8" x 25.2" (W x D x H) (695 mm x 655 mm x 641 mm) 217 lb. (90.0 kg) C912dn: 27.4" x 25.8" x 25.2" (W x D x H) (695 mm x 655 mm x 641 mm) 230.8 lb. (104.9 kg) C912fn: 46.9" x 25.8" x 40.5" (W x D x H) (1191 mm x 655 mm x 1028 mm) 409.4 lb. (185.7 kg) |
| Acoustics | Less than 58 dBA printing; Less than 48 dBA idle |
| Supplies ¹ | Ships with: 8,000-page Starter Print Cartridge Black, Cyan, Magenta and Yellow up to 28,000-page Photodeveloper Kit Black, Cyan, Magenta and Yellow 14,000-page Oil Coating Roller Optional supplies: 14,000-page Print Cartridge Black, Cyan, Magenta and Yellow |
| Duty Cycle | Up to 100,000 pages per month |
| Warranty | 1-year LexOnSite™; For more information on extended warranties and services, visit www.lexmark.com |

¹ Yield is based on approximately 5% coverage