

The Lexmark T522

Lexmark's powerful laser printer optimizes productivity and fills expanding needs at an exceptional value



- **Exceptional Value**
 - Fast 25-page-per-minute speed and powerful 250 MHz performance at an exceptional price
 - 1200 x 1200 dpi resolution provides professional-looking output
- **Optimal Productivity**
 - Print time of less than nine seconds to first page provides on-demand convenience and efficiency
 - Multifunction capability can be added to support copying, scanning and faxing
- **Seamless Connectivity**
 - ImageQuick™ solution enables direct PDF and image printing from the Web
 - Remote printer configuration, management and monitoring to reduce network administration costs
 - Network-ready Ethernet and standard parallel/USB models offer high-speed communication

Part Numbers

- United States
 - T522: 09H0200
 - T522n: 09H0300
 - T522dn: 09H0450
 - T522 for label applications: 09H0064
 - T522n for label applications: 09H0065
- Canada
 - T522: 09H0200
 - T522n: 09H0300
 - T522dn: 09H0450

Technology

- Monochrome laser

Speed

- Up to 25 pages per minute
- Less than 9 seconds time to first page

Print Quality

- 1200 x 1200 dpi
- 1200 image quality
- 600 x 600 dpi
- 300 x 300 dpi

Processor

- 250 MHz

Memory (std/max)

- 16MB/272MB (T522)
- 32MB/288MB (T522n)
- 32MB/288MB (T522dn)

Connectivity

- USB port standard (all models)
- Bidirectional parallel port standard (T522)
- 10BaseT/100BaseTX Ethernet standard on "n" and "dn" models
- Two internal solutions ports
- T522 supports the MarkNet™ X2000 series of external print servers
- T522 supports the MarkNet N2000 series of internal print servers
- Optional Tri-Port Adapter with RS-232/422 Serial, LocalTalk and IR Adapter ports
- Optional USB/Parallel 1284-C Interface Card
- Optional Coax/Twinax Adapter for SCS

Multifunction Options

- Lexmark X242*
- Lexmark X443*

Compatibility

- PostScript 3 emulation standard
- PCL 6 emulation standard
- PPDS Migration Tool

Font Selection

- PostScript 3 emulation
 - 156 scalable fonts
- PCL 6 emulation
 - 84 scalable fonts
 - 2 bitmapped fonts
- PPDS Migration Tool
 - 39 scalable fonts
 - 5 bitmapped fonts

Paper Handling

- Media sizes:
 - Standard support including letter, legal, A4, A5, JIS B5, executive, folio, statement, and custom sizes from 5.5" x 8.27" to 8.5" x 14"
 - Expanded custom sizes from 2.75" x 5" to 8.5" x 14" available with the Universally Adjustable Tray
- Media types:
 - Plain paper, bond, envelopes, card stock, transparencies, paper labels, dual-web labels, polyester labels and vinyl labels
- Media weights:
 - 16 lb. to 47 lb. bond
 - Up to 125 lb. card stock
- Input (std/max): 600/4,100 sheets
- Standard input sources:
 - One 500-sheet tray
 - One 100-sheet multipurpose tray
- Maximum input sources: 7
 - The 2 standard inputs plus 4 additional drawers (250-, 500-, and 2,000-sheet) in any combination, except only one 2,000-sheet input drawer may be used
 - One envelope feeder
- Output: 250 sheets
- Optional duplex unit for two-side printing
- For additional options and part numbers, see Order Information Chart on reverse side

Supplies

- The Lexmark T522 ships with
- 5,000-page** starter cartridge
- Other supplies:
- 7,500-page** Prebate™ print cartridge
 - 20,000-page** high yield Prebate print cartridge
 - 20,000-page** high yield print cartridge

Operating Systems

- Microsoft Windows 2000, Me, 98, 95, NT 4.0 or higher; UNIX, Linux and Mac OS
- For a complete list, see www.lexmark.com

Size/Weight

- 16.5" x 20.2" x 14.9" (W x D x H)
- (419 mm x 513 mm x 379 mm)
- 45 lb. (20.4 kg)

Acoustics

- 51 dBA printing
- 30 dBA idle

Duty Cycle

- Up to 120,000 pages per month

Warranty

- 1-year LexExpress

*Minimum 32MB memory required

**Yield is based on approximately 5% print coverage

Order Information Chart

Part Number	UPC	Description
United States		
09H0200	7-34646-62400-8	T522
09H0300	7-34646-62600-2	T522n
09H0450	7-34646-62850-1	T522dn
09H0064	7-34646-62064-2	T522 for Label Applications
09H0065	7-34646-62065-9	T522n for Label Applications
Canada		
09H0200	7-34646-62400-8	T522
09H0300	7-34646-62600-2	T522n
09H0450	7-34646-62850-1	T522dn
SUPPLIES		
Print Cartridges		
12A6735	7-34646-24472-5	High Yield Print Cartridge
12A6830	7-34646-24473-2	Prebate Print Cartridge
12A6835	7-34646-24474-9	High Yield Prebate Print Cartridge
12A6839	7-34646-24475-6	High Yield Prebate Print Cartridge for Label Applications
Routine Maintenance		
99A1017	N/A	Charge Roll Kit
99A1015	N/A	Transfer Roll Kit
99A0725	N/A	Label Fuser Wiper
Media		
1053740	7-34646-12769-1	Transparencies (Letter)
1053741	7-34646-12770-7	Transparencies (A4)
OPTIONS AND FEATURES		
Paper Handling Options		
11K0681	7-34646-28600-8	250-Sheet Drawer
11K0688	7-34646-28601-5	500-Sheet Drawer
11K1059	7-34646-28609-1	250-Sheet Tray
11K1060	7-34646-28610-7	500-Sheet Tray
11K0718	7-34646-28602-2	2,000-Sheet Drawer (Letter)
11K0719	7-34646-28603-9	2,000-Sheet Drawer (A4)
11K0722	7-34646-28606-0	500-Sheet Duplex Unit
11K0720	7-34646-28604-6	Envelope Feeder
11K1941	7-34646-39707-0	400-Sheet Universally Adjustable Tray
11K1942	7-34646-39706-3	400-Sheet Universally Adjustable Drawer
11K1574	7-34646-28625-1	250-Sheet Universally Adjustable Tray
11K1878	7-34646-28626-8	250-Sheet Universally Adjustable Drawer
Memory Options		
5K00013	7-34646-28612-1	4MB SDRAM
5K00014	7-34646-28613-8	8MB SDRAM
5K00015	7-34646-28614-5	16MB SDRAM
5K00016	7-34646-28615-2	32MB SDRAM
5K00017	7-34646-28616-9	64MB SDRAM
5K00119	7-34646-28621-3	128MB SDRAM
5K00115	7-34646-28617-6	2MB Flash DIMM
5K00116	7-34646-28618-3	4MB Flash DIMM
5K00117	7-34646-28619-0	8MB Flash DIMM
5K00118	7-34646-28620-6	16MB Flash DIMM
45H0001	7-34646-13653-2	Hard Disk Adapter
11K3927	7-34646-20991-5	5 + GB Hard Disk with Adapter

*Requires a serial interface, Tri-Port Adapter or External Serial Adapter
 **Minimum 32MB memory required

Part Number	UPC	Description
APPLICATIONS SOLUTIONS		
Optra Forms Solutions		
11N0040	7-34646-20731-7	Optra Forms™ Software
11N0052	7-34646-20732-4	Optra Forms Director
5K00215	7-34646-28715-9	Optra Forms 2MB Flash DIMM
5K00216	7-34646-28716-6	Optra Forms 4MB Flash DIMM
5K00217	7-34646-28717-3	Optra Forms 8MB Flash DIMM
5K00218	7-34646-28718-0	Optra Forms 16MB Flash DIMM
43H5841	7-34646-17041-3	2-Key Security*
43H5842	7-34646-17042-0	3-Key Security*
11K3928	7-34646-20992-2	Optra Forms 5 + GB Hard Disk with Adapter
Other Options		
44H0067	7-34646-24455-8	Lexmark T520/T522/T620/T622 ImageQuick Card
11K3800	7-34646-24481-7	Lexmark T520/T522/T620/T622 Bar Code Card
5K00205	7-34646-24457-2	Lexmark T520/T522/T620/T622 Card for IPDS and SCS/TNe
NETWORK CONNECTIONS		
External Print Servers		
46D0060	7-34646-30316-3	MarkNet X2011e Ethernet 10/100BaseTX – 1-Port
46D0040	7-34646-30315-6	MarkNet X2012e Ethernet 10/100BaseTX/10Base2 – 1-Port
46D0020	7-34646-30314-9	MarkNet X2031e Ethernet 10/100BaseTX – 3-Port
46D0000	7-34646-30313-2	MarkNet X2030t Token-Ring – 3-Port
Internal Print Servers		
44D0020	7-34646-17333-9	MarkNet N2000t Token-Ring
44D0000	7-34646-17332-2	MarkNet N2001e Ethernet 10/100BaseTX
44D0050	7-34646-17334-6	MarkNet N2002e Ethernet 10BaseT/2
OTHER ATTACHMENT OPTIONS		
Interface Card		
44H0034	7-34646-17045-1	USB/Parallel 1284-C Interface Card
Adapters		
1368705	7-34646-11309-0	External Serial Adapter
44H0008	7-34646-12648-9	Tri-Port Adapter – LocalTalk/Serial/Infrared
44H0009	7-34646-12650-2	Infrared Adapter
44H0011	7-34646-12699-1	Coax/Twinax Adapter for SCS
Cables		
43H5171	7-34646-13774-4	Parallel (3-Meter) 1284-C Cable
1329605	0-87944-09056-4	Parallel (10') Cable
1427498	7-34646-13068-4	Parallel (20') Cable
12A2405	7-34646-18340-6	USB (2-Meter) Cable
1038693	7-34646-21649-4	Serial (50') Cable
MULTIFUNCTION SOLUTIONS		
Furniture		
43H2950	7-34646-12679-3	T Printer Stand with Cabinet
11K2036	7-34646-39600-4	T Printer Stand
43H5250	7-34646-13845-1	T Low Profile Printer Stand
11K3306	7-34646-21008-9	MFP Stand
16A0805	7-34646-36703-5	MFP Adjustable Stand
16A0503	7-34646-26665-9	T Scanner Shelf
11K2037	7-34646-13861-1	Scanner Stand with Cabinet
Multifunction Options		
16A0470	7-34646-26670-3	Lexmark X242**
16A0533	7-34646-20597-9	Lexmark X443**

Lexmark, Lexmark with diamond design, MarkNet, and Prebate are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. ImageQuick, and Optra Forms are trademarks of Lexmark International, Inc. LexExpress and LexOnSite are service marks of Lexmark International, Inc. Adobe is a trademark of Adobe Systems Incorporated. PostScript is a registered trademark of Adobe Systems Incorporated. Operating System/2, AIX, Application System/400, OS/400, Operating System/400, RISC System/6000 are registered trademarks of the International Business Machines Corporation. Microsoft and Windows are registered trademarks of the Microsoft Corporation. Windows NT is a trademark of the Microsoft Corporation. IBM is a registered trademark of International Business Machines Corporation in the United States and/or other countries and is used under license. PCL, HP and LaserJet are registered trademarks of the Hewlett-Packard Company. PS/2 is a registered trademark of International Business Machines Corporation. Apple AppleTalk, LocalTalk and Macintosh are trademarks of Apple Computer, Inc. PANTONE and PANTONE CALIBRATED are registered trademarks of Pantone, Inc. Impressario and IRIX are trademarks of Silicon Graphics, Inc.



©2001 Lexmark International, Inc.
 Printed in the United States of America 6/01
 All Rights Reserved
 71K-6302
 PC30238