

7265 Serial Matrix

Reliability At A Top Speed Of Up To 900 CPS



Top Speed Of Up To 900 CPS.

At a top speed of 900 characters per second, the 7265 keeps pace with the hectic business world where printing is time sensitive and critical. The 7265 produces multi-part invoices, shipping documents or bar code labels at a rate of 40,000 pages per month.

The 7265 is expandable to two front input tractors and can handle up to 7-part forms with a straight paper path resulting in jam-free operation.

Ideal For Many Markets & Applications.

Federal, State & Local Government can print tax forms, payroll checks, expense reports, inventory reports, invoices. TallyGenicom—a well-known vendor to government installations—is an ISO 9001 certified manufacturer. Straight paper path for unattended, jam-free operation.

Manufacturing, Transportation, & Distribution can Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET. Energy Star compliant and low-cost to own and operate. Rugged design for harsh environments.

Product Highlights

900 characters per second/540 pages per hour in draft mode
Near letter quality printing at 300 characters per second!
Straight paper path for reliable forms handling.
Up to 6-part forms with no skewing or jamming.
Automatically adjusts for different forms thickness.
Automatic quick-tear.
Long life, 20 million character ribbon for less operator interventions.
Parallel standard.
10/100 Ethernet and Serial optional.
Monthly workload of up to 40,000 pages per month.
Five configurations stored in non-volatile memory.

Available Configuration:

7265 - 24-wire, Parallel

Features & Specifications

Print Speed	15 cpi:900/300/150; 12 cpi:720/240/120; 10 cpi:650/200/100 (Draft/NLQ/LQ)
Print Method	Serial Impact Dot Matrix; 136 Column; 5 stored configurations
Resolution	360 x 360 dpi
Throughput	540 pages per hour (ECMA 132/6.91, draft)
Character Density	10,12,15,17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 M Characters (draft)
Standard Connectivity	Bi-directional Centronics Parallel
Optional Connectivity	10/100 Ethernet, RS232 Serial
Standard Emulation	GENICOM ANSI, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL
Fonts	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts
Consumables	20 M Character Ribbon
STD Paper Handling	Front insertion, Push tractor with paper parking and AGA
Opt'l Paper Handling	Additional front push tractor.
Number of Copies	6-part forms
Paper Type	Continuous
Paper Weight	NA
Paper Size	NA
Physical Weight	42 lbs.
PhysicalSize	24.5" x 10.9" x 16.9"
Power Voltage	AC 230V, 50/60Hz and 120V, 60Hz (selectable)
Power Consumption	60 Watts
Compliance	Energy Star compliant, Ozone-free.
Workload	Up to 40,000 pages per month
Reliability MTBF	10,000 hours @ 25% duty cycle
Drivers	Windows XP, 2000, 2003 Server, 95/98, NT4
Temperature	+10°C to +35°C
Humidity	16% to 73%
Acoustic	53 dB (ISO 7779)
Warranty	One year limited on site. First 90 days - parts, labor and travel
Option 1	RS232 Serial; 10/100 Ethernet
Note	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Published Date: 05/04/2006 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com

