

LA800 Serial Matrix

Like Having Two Printers In One



Class-leading performance.

At top speeds of 1,100 characters per second, the LA800 keep pace with the bustling, no-nonsense world where printing is time sensitive and critical. These devices produce multi-part invoices, shipping documents or bar code labels at a rate of 50,000 pages per month.

The addition of a second front push tractor allows two sets of different forms to be loaded simultaneously, making the printer accessible to multiple users from several applications without having to reload paper. And zero-inch tear-off reduces paper waste and decreases paper cost. This dual fanfold capability with standard and optional push tractors allows the LA800 printer to perform the tasks of two printers.

Ideal For Many Markets & Applications.

Federal, State & Local Government - Print tax forms, payroll checks, expense reports, inventory reports, invoices. Manufacturing, Transportation, & Distribution - Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET. Healthcare - Handles a wide variety of media including bar code labels for patient charts, prescription labels, pre-printed forms for billing departments.

Product Highlights

1,100 characters per second/600 pages per hour in draft mode
Near letter quality printing at 370 characters per second.
Straight paper path for reliable forms handling.
Up to 7-part forms with no skewing or jamming.
Automatically adjusts for different forms thickness.
Load two forms at once with optional second tractor.
Automatic quick-tear.
Long life, 20 million character ribbon for less operator interventions.
Excellent Connectivity - Serial and parallel standard.

Available Configuration:

LA800 Serial Matrix Printer - 880 cps (12cpi)

Features & Specifications

Print Speed	At 10,12,15 cpi: Draft:800,880,1100; NLQ:245,295,370; LQ:120,145,185
Print Method	Serial Impact, Bi-directional
Resolution	360 x 360 dpi
Throughput	600 pages per hour (ECMA 132/6.91, draft)
Character Density	10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Standard Connectivity	Bi-directional Centronics Parallel and RS-232 Serial (auto-switching), 128K buffer
Optional Connectivity	Internal 10/100 Ethernet Interface, MPS100-01 10/100BaseT Ethernet Print Server (110v)
Standard Emulation	DEC ANSI PPL2, IBM® Proprinter XL24e, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2)
Fonts	Draft, Copy Draft, Courier, Roman, San Serif, OCR A/B, 15 Bar codes & scaleable LCP font
Consumables	20 million characters ribbon
STD Paper Handling	Front insertion, Push tractor with paper parking and AGA
Opt'l Paper Handling	Additional front push tractor
Number of Copies	Front: 7-part forms; Rear: 3-part forms
Paper Type	Continuous Forms
Paper Weight	NA
Paper Size	NA
Physical Weight	42 lbs
PhysicalSize	24.5" x 10.9" x 16.9"
Power Voltage	AC 230V, 50/60Hz and 120V, 60Hz (selectable)
Power Consumption	60 watts
Compliance	Energy Star compliant, Ozone-free.
Workload	40,000 pages per month
Reliability MTBF	10,000 hours @ 25% duty cycle
Drivers	Windows 95/98, 2000, XP, NT 4.0
Temperature	+10°C to +35°C
Humidity	16% to 73% (relative humidity)
Acoustic	53 dB(A)
Warranty	Limited Onsite (90 days parts, labor, travel. Remainder of the year, parts only)
Option 1	front push tractor
Option 2	pedestal cabinet, printer stand, paper basket, castors
Option 3	Internal 10/100 Ethernet Interface, MPS100-01 10/100BaseT Ethernet Print Server (110v)
Options 4	9- to 25-Pin Serial Adapter
Note	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Published Date: 05/04/2006 Copyright © 2006 TallyGenicom, L.P.



4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com

